



Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 11261582
Procuring Entity BUREAU OF FISHERIES AND AQUATIC RESOURCES CARAGA
Title RFQ-For regular monitoring of SHELLFISH TECHNO DEMO PROJECT in PDI
Area of Delivery Agusan Del Norte

Solicitation Number:	RFQ-158-2024	Status	Pending
Trade Agreement:	Implementing Rules and Regulations	Associated Components	1
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification:	Goods	Document Request List	0
Category:	Laboratory Supplies and Equipment	Date Published	18/09/2024
Approved Budget for the Contract:	PHP 110,000.00	Last Updated / Time	17/09/2024 16:41 PM
Delivery Period:	30 Day/s	Closing Date / Time	24/09/2024 17:00 PM
Client Agency:			
Contact Person:	Elvera Base Sayas BAC Secretariat Peñaranda Street, Barangay Taft Surigao City Surigao Del Norte Philippines 8400 63-909-4817511 bac.caraga@bfar.da.gov.ph		

Description

Note:

- For queries and requesting (RFQ) form
- visit our website (Caraga.bfar.da.gov.ph)
- Standard form of our RFQ form shall be accepted, herewith attached in post to the PHILGEPS.
- Submit your quotation seal and label with reference number/project title, at B FAR 13 SURIGAO CITY, SURIGAO DEL NORTE
- Attach for the following requirements:
 1. PHILGEPS REGISTRATION
 2. BUSINESS PERMIT
 3. Certificate of Registration (BIR)
 4. Omnibus Sworn Statement

Unit Description Qty

1 pcs "Pen type tester for pH, With warranty and demonstration: pH Range: -2.00 to 16.00 pH;

Resolution: 0.01/0.1 pH

Accuracy: ±0.01 pH ±1 digit

Calibration Points; Automatic 1 to 3 points (recognizes 5 types: 7.00, 4.00, 10.01, 1.68, 12.46)

Temperature Compensation: Auto Temperature Compensation

0 to 50°C (32 to 122°F); ORP(mV) Range; ±1000 mV

Resolution: 1 mV

Accuracy; ±0.2% F.S

Temperature Range: 0 to 50°C (32 to 122°F)

Resolution: 0.1°C

Accuracy: ±0.5°C

LCD: 3-Color Backlit LCD, 180° Viewing Angle Blue: Measurement Mode; Green: Calibration Mode; Red: Heads-Up Mode

Reading Lock :HOLD

Stable Reading Indication: Smiley Face icon

Low-Battery Warning: Battery icon flashing, reminder of battery replacement

Self-Diagnosis: Yes
Heads-Up Function; Yes
Auto. Power-Off: Yes, auto power-off in 8 minutes without operation
Waterproof Rating: IP67; Floatable
Power; DC3V, AAA batteries*4
Battery Life: Continuous operation up to 2000 hours
Dimensions& Weight Tester: (40*40*178) mm/ 133g With case_(255*210*50) mm/
700g Electrode's Technical Specs
Application: Regular water solution testing, such as pools and spas, hydroponics, tap water,
drinking water, water treatment, aquaculture, cooling towers, etc.
Shape of glass membrane: Bulb
Replaceable: Yes
Temperature sensor: Yes
Junction: Single Junction Ceramic
Reference Eelctrode: Ag/AgCl
Electrolyte; KCL Gel
Range: 0 to 14 pH
Temperature Range: 0 to 50°C (32 to 122°F)" 5
2 pcs "Pen type saltwater salinity tester, With warranty and demonstration: Dip and test - the easiest way to get
reliable saltwater salinity
readings (range: 0-100 ppt; accuracy:1.5% of full range)
• unique platinum-coated sensor with automatic temperature
compe nsation (32 to 140 °F) ensures accuracy and precision
• Standardized against the normal standard seawater (s = 35), accurately
calibrated in conductivity ratio (K15) and in salinity
• Designed for saltwater aquariums, fish farms, and environmental monitoring
• Single-button easy operation. Calibration is only needed once a month " 5
3 pcs "Refractometer, Attribute
Value
Refractometer Type Mix Cutting Fluids
Maximum Measurement 18%
Minimum Measurement 0%
Best Accuracy ±0.1 %
Resolution 0.1 %Brix
Dimensions 96 x 60 x 230mm
Weight 525g
Height 60mm
Length 230mm
Width 96mm" 2

Created by Elvera Base Sayas

Date Created 17/09/2024

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.